

3.2m Grand format Dye-Sub Textile Printer

FABRIJET Series

FTII-3204D



Speed 120 m²/hr

Print Width 3.2 m

Resolution **1,440** dpi **Print Head** 4color 8head





GRAND SIZE DYE SUBLIMATION TEXTILE SOLUTION FOR MASS PRODUCTION





TECH 1

Platen vacuum control system

Designed to control media feeding with vacuum air to make pricise printing



TECH 2

Built in media drying unit

For great performance of printing, adopted built in drying system



TECH 3

One touch capping system

Designed to preserve printhead great condition at all time



TECH 4

3.8L Ink tank

For mass production, 3.8L ink tank makes you less refill during printing

Technical Specification







ISO 9001:14001 Certified

(Print Speed)	Draft Mode 120 m²/hr Production Mode 60 m²/hr Quality Mode 40 m²/hr High Quality Mode 30 m²/hr
(Print Resolution)	720 x 360dpi (2 Pass) 720 x 720dpi (4 Pass) 720 x 1,080dpi (6 Pass) 720 x 1,440dpi (8 Pass)
(Max Print Width)	3,200 mm
(Max Media Width)	3,250 mm
(Media)	
Handling Type Head Height Max Weight	Roll to sheet Transfer paper 2.5mm~4.4mm 100 Kg
(Print Mode)	2 Pass, 4 Pass, 6 Pass, 8 Pass (Bidirectional) / (Unidirectional)
(Printhead)	Konica Minolta New technology head / 8
(Color)	(4 Color) - Cyan, Magenta, Yellow, Black
(lnk)	(Dye Sublimation Ink)
(Interface)	TCP / IP
(Dimension)	(Uncrated): 4,900(L) x1,020(W) x1,550(H) (Crated): 5,200(L) x1,250(W) x1,880(H)
(Weight)	(Uncrated): 940Kg (Crated): 1,640Kg
(Environmental Range)	(Temperature) : 20~30 °C (Humidity) : 45~60% If environmental range is not on the recommended value, it may cause machine failure or makes poor printing qualit
(Electricity Requirements)	Single Phase 220V(50/60Hz,AC), 30A, 6.6KW

All specifications are subject to change without notice.



DGI FTII-3204D bros-AB-110314

52, Cheongdam-Ro, Yangju-si, Gyeonggi-do, Korea, 482-020 TEL:+82-31-820-8900 A/S:+82-31-820-8880 FAX:+82-31-820-8990 E-MAIL:sales@dgi-net.com

www.dgi-net.com



Italian distributor

Trend s.r.l. / Via Mario Corrieri, 12 - 05100 Terni (TR), Italy / Phone: (+39) 0744 800680 Fax: (+39) 0744 800514

Email: commerciale@trendsrl.net