



1.9m Wide Direct Textile Printer
FABRIJET SERIES

FD-1904

Speed
140 m²/hr

Print Width
1.9m

Resolution
1,200 dpi

Print Head
8 color
4 head



Creative Technology, Reliability and Support, the Future by DGI


HIGH VALUED DIGITAL TEXTILE PRINTING



TECH 1

Kyocera 2656 nozzle heads


The state of the art head in the market guarantee of high performance and high quality digital printing



TECH 2

Belt Cleaning System

The device clean the belt with water



TECH 3

Wrinkle Detecting sensor

Printing will stop when sensor detects any wrinkle on the belt



TECH 4

Obstacle Detecting System

Wing Sensor for preventing fabrics crushing

Technical Specification



ISO 9001:14001 Certified

(Print Speed)	Draft Mode 140 m ² /hr	Production Mode 80 m ² /hr	Quality Mode 50 m ² /hr	High Quality Mode 25 m ² /hr
(Print Resolution)	540 x 360dpi (1 Pass)	540 x 720dpi (2 Pass)	540 x 1,080dpi (3 Pass)	540 x 1,200dpi (4 Pass)
(Max Print Width)	1,900 mm			
(Max Media Width)	1,900 mm			
(Print Mode)	(Bidirectional), (Unidirectional)			
(Printhead)	KYOCERA 2656 nozzles (300dpi)			
(Color)	(8 Color) - Cyan, Magenta, Yellow, Black, Blue, Red, Orange, Gray			
(Ink)	(Acid, Reactive, Disperse)			
(Interface)	TCP / IP			
(Dimension)	(Uncrated) : 4,700(L) x 2,080(W) x 1,650(H) (Crated) : 5,800(L) x 1,660(W) x 2,100(H)			
(Weight)	(Uncrated) : 2,000 Kg (Crated) : 2,750 Kg			
(Neumatics)	Min5 kgf/cm ²			
(Environmental Range)	(Temperature) : 20~30°C (Humidity) : 45~60%			
	If environmental range is not on the recommended value, it may cause machine failure or makes poor printing quality			
(Electricity Requirements)	220~240V VAC Single Phase, 50/60 Hz			

All specifications are subject to change without notice.



DGI FD-1904 bro-AB-110314
52, Cheongdam-Ro, Yangju-si, Gyeonggi-do, Korea, 482-020
TEL : +82-31-820-8900 A/S : +82-31-820-8880
FAX : +82-31-820-8990 E-MAIL : sales@dgi-net.com
www.dgi-net.com



Italian distributor

Trend s.r.l. / Via Mario Corrieri, 12 - 05100 Terni
(TR), Italy / Phone: [+39] 0744 800680
Fax: [+39] 0744 800514
Email: commerciale@trendsril.net